

FEATURES

- Low profile and thin thickness.
- Monolithic structure for high reliability.
- Closed magnetic circuit design reduces leakage flux and EMI.
- Operating temperature: -40°C ~ +85°C.



APPLICATIONS


- DC-DC converter circuits for mobile phones, wearable devices, DVCs, HDDs, etc.

PRODUCT IDENTIFICATION

MCPI 201610 H 1R0 M T
 (1) (2) (3) (4) (5) (6)

- (1) 系列名称 Series name
- (2) 产品尺寸 Product dimensions
- (3) 特性类别 Feature Type (S: Standard Type, H: High Current Type)
- (4) 电感量 Inductance Value (1R0:1.0uH, 100:10uH, 101:100uH)
- (5) 电感公差 Inductance Tolerance(K:10%, M:20%, N:30%)
- (6) 包装 Package(T:Tape&Reel 卷盘编带)

SHAPE AND DIMENSIONS



Series	L	W	T	D
MCPI160808	1.6±0.2	0.8±0.2	0.8±0.2	0.3±0.2
MCPI201210	2.0±0.2	1.2±0.2	0.9±0.2	0.5±0.3
MCPI201610	2.0±0.2	1.6±0.2	0.9±0.2	0.5±0.3
MCPI252010	2.5±0.2	2.0±0.2	1.0±0.2	0.5±0.3

Unit:mm

SPECIFICATIONS

MCPI160808 Series

Part Number	Inductance (μH)	Tolerance (%)	Test Condition	DCR (Ω)	SRF Min. (MHz)	Irms (mA)
MCPI160808HR47MT	0.47	20	1MHz/1V	0.10 \pm 30%	100	1050
MCPI160808HR56MT	0.56	20	1MHz/1V	0.12 \pm 30%	100	1050
MCPI160808H1R0MT	1.0	20	1MHz/1V	0.20 \pm 30%	98	900
MCPI160808H1R8MT	1.8	20	1MHz/1V	0.24 \pm 30%	95	750
MCPI160808H2R2MT	2.2	20	1MHz/1V	0.24 \pm 30%	95	750
MCPI160808H4R7MT	4.7	20	1MHz/1V	0.50 \pm 30%	65	700

MCPI201210 Series

Part Number	Inductance (μH)	Tolerance (%)	Test Condition	DCR (Ω)	SRF Min. (MHz)	Irms (mA)
MCPI201210S1R0MT	1.0	20	1MHz/1V	0.14 \pm 25%	75	300
MCPI201210S2R2MT	2.2	20	1MHz/1V	0.224 \pm 25%	50	220
MCPI201210S3R3MT	3.3	20	1MHz/1V	0.24 \pm 25%	35	200
MCPI201210S4R7MT	4.7	20	1MHz/1V	0.30 \pm 25%	25	180
MCPI201210H1R0MT	1.0	20	1MHz/1V	0.11 \pm 25%	75	1150
MCPI201210H2R2MT	2.2	20	1MHz/1V	0.20 \pm 25%	50	950
MCPI201210H3R3MT	3.3	20	1MHz/1V	0.22 \pm 25%	35	800
MCPI201210H4R7MT	4.7	20	1MHz/1V	0.30 \pm 25%	25	750
MCPI201210H6R8MT	6.8	20	1MHz/1V	0.30 \pm 25%	25	600

MCPI201610 Series

Part Number	Inductance (μH)	Tolerance (%)	Test Condition	DCR (Ω)	SRF Min. (MHz)	Irms (mA)
MCPI201610H1R0MT	1.0	20	1MHz/1V	0.10 \pm 25%	70	1400
MCPI201610H2R2MT	2.2	20	1MHz/1V	0.16 \pm 25%	50	1200
MCPI201610H3R3MT	3.3	20	1MHz/1V	0.20 \pm 25%	40	1200
MCPI201610H4R7MT	4.7	20	1MHz/1V	0.26 \pm 25%	30	1100

MCPI252010 Series

Part Number	Inductance (μH)	Tolerance (%)	Test Condition	DCR (Ω)	SRF Min. (MHz)	Irms (mA)
MCPI252010H1R0MT	1.0	20	1MHz/1V	0.06 \pm 25%	70	1600
MCPI252010H2R2MT	2.2	20	1MHz/1V	0.10 \pm 25%	55	1300
MCPI252010H3R3MT	3.3	20	1MHz/1V	0.14 \pm 25%	30	1200
MCPI252010H4R7MT	4.7	20	1MHz/1V	0.18 \pm 25%	25	1100

Note:

Irms: DC current that causes the temperature rise($\Delta T=40^{\circ}\text{C}$) from 25°C ambient.